

# Model 175 | V6

## Specifications



175  
V6

|                               |   |
|-------------------------------|---|
| Model                         | a. E175DPL<br>b. E175DSL<br>c. E175DPX<br>d. E175DCX                                |
| Shaft Length mm (in) / Color  | a. 508 (20") Blue<br>b. 508 (20") White<br>c./d. 635 (25") White                    |
| Weight kg (lbs)               | a./b. 190 (419)<br>c./d. 194 (427)  |
| Engine Type                   | Loop Charged V6 60° E-TEC D.I.  |
| Bore x Stroke mm (in)         | 91 x 66 (3.600 x 2.588)   |
| Displacement cc (cu in)       | 2589 (158)  |
| Starting                      | Electric  |
| Trim Method                   | FasTrak™ Power Trim and Tilt  |
| Propshaft kilowatts* (HP)     | 131 kw (175 HP)<br>@ 5000 RPM   |
| Full Throttle Operating Range | 4750-5750 RPM   |
| Gear Ratio                    | a./b. 1.86:1<br>c./d. 1.85:1  |
| Fuel Induction                | E-TEC Direct Fuel Injection with stratified low RPM combustion mode                 |
| Alternator                    | Variable Voltage Computer Controlled<br>133 Amp** / 1800 watt output with Regulator |
| Cooling                       | Pressure and Temperature<br>Controlled Water Cooled                                 |
| Steering                      | Remote  |
| Limited Warranty              | 3 Years Non-Declining   |
| Emissions Compliance          | EPA 2006<br>CARB 3 STAR<br>European Union 2006                                      |

