

# Model 200 H.O. | V6

## Specifications



**200**  
H.O.  
V6

Model	a. E200DHL b. E200HSL c. E200DHX d. E200HCX
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White c./d. 635 (25") White
Weight kg (lbs)	a./b. 231 (509) c./d. 238 (524)
Engine Type	Loop Charged V6 90° E-TEC Direct Injection (D.I.)
Bore x Stroke mm (in)	98 x 73 (3.854 x 2.858)
Displacement cc (cu in)	3279 (200)
Starting	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts* (HP)	FactoryTuned for High Performance
Full Throttle Operating Range	4500-5800 RPM
Gear Ratio	a./b. 1.86:1 High Speed c./d. 1.85:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA 2006 CARB 3 STAR European Union 2006



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.  
\*\* 133 Amp current calculated at 13.5 V.  
Net dedicated battery charging power output is 50 Amp.