

Model 40

Specifications



40

| | |
|-------------------------------|--|
| Model | a. E40DPL b. E40DEL c. E40DRL |
| Shaft Length mm (in) / Color | a. 508 (20") Blue b. 508 (20") Blue c. 508 (20") Blue |
| Weight kg (lbs) | a. 109 (240) b. 104 (230) c. 105 (232) |
| Engine Type | Inline 2-cylinder E-TEC D.I. |
| Bore x Stroke mm (in) | 91 x 66 (3.600 x 2.588) |
| Displacement cc (cu in) | 863 (52.7) |
| Starting | a./b. Electric c. Rope |
| Trim Method | a. Power Trim and Tilt b./c. Manual Tilt |
| Propshaft kilowatts* (HP) | 30 kw (40 HP) @ 5500 RPM |
| Full Throttle Operating Range | 5000-6000 RPM |
| Gear Ratio | 2.67:1 |
| Fuel Induction | E-TEC Direct Fuel Injection with stratified low RPM combustion mode |
| Alternator | Variable Voltage Computer Controlled 75 Amp** / 1100 watt output with Regulator |
| Cooling | Pressure and Temperature Controlled Water Cooled |
| Steering | a./b. Remote or Acc. Tiller c. Tiller Standard |
| Limited Warranty | 3 Years Non-Declining |
| Emissions Compliance | EPA 2006 CARB 3 STAR European Union 2006 |

