

Model 60

Specifications



Model	E60DPL
Shaft Length mm (in) / Color	508 (20") Blue
Weight kg (lbs)	109 (240)
Engine Type	Inline 2-cylinder E-TEC D.I.
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	863 (52.7)
Starting	Electric
Trim Method	Power Trim and Tilt
Propshaft kilowatts* (HP)	45 kw (60 HP) @ 5750 RPM
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	2.67:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 75 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA 2006 CARB 3 STAR European Union 2006

©2005 Bombardier Recreational Products Inc. All rights reserved. **Trademark of Bombardier Recreational Products Inc. or its affiliates.



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.
** 75 Amp current calculated at 13.5 V.
Net dedicated battery charging power output is 25 Amp.