

# Model 75

## Specifications



75

|                               |  |
|-------------------------------|--|
| Model                         | E75DPL   |
| Shaft Length mm (in) / Color  | 508 (20") Blue   |
| Weight kg (lbs)               | 145 (320)  |
| Engine Type                   | Inline 3-cylinder E-TEC D.I.   |
| Bore x Stroke mm (in)         | 91 x 66 (3.600 x 2.588)  |
| Displacement cc (cu in)       | 1295 (79)  |
| Starting                      | Electric   |
| Trim Method                   | FasTrak™ Power Trim and Tilt   |
| Propshaft kilowatts* (HP)     | 56 kw (75 HP)<br>@ 5000 RPM  |
| Full Throttle Operating Range | 4500-5500 RPM  |
| Gear Ratio                    | 2.0:1  |
| Fuel Induction                | E-TEC Direct Fuel Injection with stratified<br>low RPM combustion mode             |
| Alternator                    | Variable Voltage Computer Controlled<br>75 Amp** / 1100 watt output with Regulator |
| Cooling                       | Pressure and Temperature<br>Controlled Water Cooled                                |
| Steering                      | Remote or Accessory Tiller   |
| Limited Warranty              | 3 Years Non-Declining  |
| Emissions Compliance          | EPA 2006<br>CARB 3 STAR<br>European Union 2006                                     |

©2005 Bombardier Recreational Products Inc. All rights reserved. \*\*Trademark of Bombardier Recreational Products Inc. or its affiliates.



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMIA) standard 28/83.  
\*\* 75 Amp current calculated at 13.5 V.  
Net dedicated battery charging power output is 25 Amp.